

## **BCP-DGKat623**

Four-Pair F/UTP Data Bulk Cable (23AWG) – Plenum Rated



Kramer's BCP-DGKat623 is a plenum rated shielded twisted pair (STP) cable, the ideal companion to Kramer's twisted pair digital transmitter-receiver sets for optimum range and performance

### **FEATURES**

Quality Construction - 4 twisted pairs of 23 AWG solid copper conductors are cabled together and shielded with a polyesteraluminum tape and outer jacket

Optimized for Kramer Hardware - Use with any of Kramer's wide range of twisted pair digital transmitterreceiver sets. Terminate with shielded RJ45 connectors

System Range - 295' (720p/1080i @ 60Hz) & 230' (1080p @60Hz)

Varied Selection of Length - Available in pull boxes of 152m (500ft) & 305m (1000ft)



### TECHNICAL SPECIFICATIONS

#### CONSTRUCTION

Pair Color Code Chart 1: Whilte/Blue Stripe & Blue

2: White/Orange Stripe & Orange 3: White/Green Stripe & Green 4: White/Brown Stripe & Brown

Outer Jacket Color Black

Outer Jacket Ripcord: for easy jacket stripping

Polyvinyl chloride 0.20 wall thickness

**Outer Jacket** 

Diameter

0.285 Inches

Total wires 4 shielded twisted pairs

**Braided Shield** 38 AWG tinned copper, 65% minimum coverage

Conductor Color code Blue/white, brown/white, green/white, orange/white

**ELECTRICAL** 

Max. Conductor

Resistance

27/1000ft

Maximum Resistance 5%

Unbalanced

Mutual Capacitance

Unbalanced

160pF/100m @1kHz

Pair to Pair Skew 12ns/100m max

Capacitance (Cond-

Cond)

40pF/m nominal

REGULATORY

**RoHS Compliant** 



# **CONFIGURATIONS**

BCP-DGKat623-500 Four-Pair F/UTP Data Bulk Cable (23AWG) - Plenum Rated

BCP-DGKat623-1000 Four-Pair F/UTP Data Bulk Cable (23AWG) - Plenum Rated