

DATA SHEET

IMPERA ECHO PLUS

8-BUTTON CONTROL PAD WITH ETHERNET PORT



The Impera Echo Plus control pad is a compact, highly customizable AV control suitable for wall-mounting or installation in the EasyConnect tabletop cable management solution. It provides a simple and intuitive interface for presentation spaces, learning environments, and conference rooms, regardless of the type of equipment installed.

The Echo Plus can be quickly programmed and customized within Project Designer as the needs of the room change over time, making it a very flexible and cost effective control solution.

FEATURES

- Supports up to 8 software-configurable buttons
- Includes on-board controller; no external processor required
- Controls up to 2 third party devices over Ethernet
- 1 bi-directional RS-232/IR port for third party control with feedback
- 1 uni-directional RS-232/IR port for third party control
- 3 GPIO ports
- Micro USB connection for system configuration and maintenance
- Supports email notifications for lamp/filter hours and warnings
- Expansion Bus supports up to 2 additional devices (keypads and port expanders)
- Covered by Biamp Systems' five-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The control pad shall include 8 mechanical buttons for initiating control functions. The control pad shall include 8 multicolor, software configurable LEDs. Each mechanical button shall have a corresponding LED. The control pad shall utilize an Ethernet network via an RJ-45 connector for networking as well as software configuration and control. The control pad shall include 1 bi-directional RS-232/IR port for controlling third party devices with feedback functionality and shall be software programmable. The control pad shall include 1 uni-directional RS-232/IR port for controlling third party devices and shall be software programmable. The control pad shall include 3 channels of General Purpose Input and Output connection (GPIO) for sending or receiving logic signals. The programming of the GPIO ports shall be software configurable. The control pad shall be CE marked and compliant with the RoHS directive. Warranty shall be five years. The control pad shall be the Impera Echo Plus.

IMPERA ECHO PLUS SPECIFICATIONS

Control		Power:	12V DC 5W
Button Quantity:	8	EU Model Dimensions	
Button Type:	Mechanical	Height:	2.2 inches (55 mm)
LED Indicators:	Multi-color	Width:	2.2 inches (55 mm)
		Depth:	0.7 inches (17 mm)
Ethernet		DK Model Dimensions	
Port Speed:	10/100 Mbps	Height:	1.8 inches (45 mm)
Autosense:	Yes	Width:	2.8 inches (72 mm)
Number of Devices Supported:	2	Depth:	0.7 inches (17 mm)
GPIO		US Model Dimensions	
I/O Quantity:	3	Height:	4.1 inches (105 mm)
Sense Low:	< 1 VDC	Width:	1.8 inches (45 mm)
Sense High:	> 4 VDC	Depth:	0.9 inches (24 mm)
Output Type:	Open drain	Weight:	0.20 lbs (90 g)
Max Voltage:	24 VDC		
Max Current:	0.5 A	Environmental	
RS-232 / IR		Ambient Operating	
Number of Ports:	1 (bidirectional) 1 (unidirectional)	Temperature Range:	32 - 104° F (0 - 40° C)
Baud Rate:	1200 - 115200 bit/sec	Humidity:	10-90% relative humidity (non-condensing)
Data Bits:	7, 8	Altitude:	0-6,600 ft (0-2000m) MSL
Parity:	Even, Odd, None	Compliance	
Stop Bits:	1, 1.5, 2		CE Marked (Europe)
IR Frequency Range:	381 Hz to 500 kHz		RoHS Directive (Europe)
Expansion Bus			
Output Power:	12 V DC (0.3 A)		
Number of Devices Supported:	2		

IMPERA ECHO PLUS REAR PANEL (EU MODEL)



IMPERA ECHO PLUS MODELS

8DKW	DK form factor, white
8DKB	DK form factor, black
8EUW	EU form factor, white
8EUB	EU form factor, black
8USW	US form factor, white

Biamp and Impera are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.