

COMMUNICATION AMPLIFIERS

iCOMC Communication Amplifiers

Two channel communication amplifiers with RS232 interface and IR remote control.

iCOMC 2x20

iCOMC 2X20 two channel communication amplifiers with RS232 interface and IR remote control. Designed for small size applications. D class power amplifier, limiter, stereo and bridge mode, tone control, line input, balanced microphone input, phoenix output connector, phantom power and loudness function. Some of functions can be controlled by using IR remote control or RS232. Suitable to be mounted on any flat surface, horizontal or vertical. External power supply



Optional accessory - IR remote control

Technical Specifications	iCOMC 2x20
Output power	2 x 20 W
Power supply	24 V DC 1,5 A
Outputs	Low impedance output - 4 Ω (screw terminal block)
Inputs	Mic: Sensitivity -60 dBu Connector - Balanced Phoenix Line 1: Sensitivity -7 dBu Connector - 3,5 mm stereo Jack Line 2: Sensitivity -7 dBu Connector - Stereo RCA
Frequency response	35 Hz - 20 kHz
THD	< 0,03 %
Signal / noise ratio	> 100 dB
Tone control	Bass ± 7 dBu , Treble ± 7 dBu
Controls	Mic and Line input level controls, balance control, tone control, input selector, loudness, limiter and phantom power. RS 232 and IR remote controls.
Indicators	Power, volume, balance, tone
Dimensions	145 mm x 120 mm x 45 mm
Weight	0,6 kg