



# ENTERTAINMENT STAGE & CLUB

## LEDWASH SERIES

### GENERAL INFORMATION

The CLF LEDWash is a truly unique fixture. It can be used for all sorts of wall washing purposes, the extreme flat dimensions makes it the ideal tool for use on catwalks, stages, live performances, decors of TV shows and all sorts of other events.

With the powerful RGBW 4 in 1 chips and the use of the 50 mm reflector a high quality colour mixing is being achieved. The version with dynamic white is able to generate a broad range of white light varying from 2700K to 7200K.

Due to the CLS camlock system the LEDWash can not only be used as a free standing floor fixture but

also easily be mounted in a truss. The beam can be rotated almost 180° for a optimized covering of the area.

The CLF LEDWash can be used as a wall washer for heights up to 8-10 meter. The units come standard with a slightly frosted front plate. Should a even higher light output be required than the front plate can be changed into a clear one that increases the light output by another 12%.

The LEDWash has apart from DMX in/outputs, several stand alone operation modes.



### MAIN FEATURES

- **Very even colour mixing**
- **XLR 3 and 5** pin data connectors
- **Powercon** in/out
- **Power cable** Included
- **Extreme flat** dimensions
- **CLS camlock** system
- **Floor standing use & truss mounting**

## SPECIFICATIONS

Item	LEDWash RGBW	LEDWash CW-WW
LEDs	9 x 4 in 1	9 x 2 in 1
Colour	RGBW	Cold white + warm white
Lenses	50°	50°
Power supply	Voltage: 100 ~ 240 VAC	Voltage: 100 ~ 240 VAC
Power consumption	Max. 65 Watt	Max. 50 Watt
Cos φ	0.67	0.67
Weight	3.5 kg	3.5 kg
Measurements	140 x 480 x 105 mm (hxwxd)	140 x 480 x 105 mm (hxwxd)
Control in & output	XLR3 or XLR5 pole male-female	XLR3 or XLR5 pole male-female
Channels	3, 4, 5, 6 or 11 channels maximum	2, 3 or 7 channels maximum
Connectionl	Powercon in and out	Powercon in and out
Modes	DMX512, Stand alone or Master/Slave mode	DMX512, Stand alone or Master/Slave mode
IP value	IP20	IP20
Housing	Aluminum	Aluminum
LED current	550 mA	660 mA
Colour temperature	- -	2800K ~ 7200K
CRI	- -	>90Ra
Frontplate	Clear or Frost (included)	Clear or Frost (included)



## ACCESSORIES

- CLS Clamp # 875760