

# MICPAT-2

Selective 2-zone paging station



The MICPAT-2 is a sturdy table type paging microphone. It is ideal for use with CONCEPT1(T) and MA247(MR).

It has a flexible gooseneck and a high quality unidirectional dynamic microphone capsule. With MICPAT-2 you can make paging calls to maximum two zones simultaneously (zone 1 individual, zone 2 individual or both zones).

A clear LED indication for both the zones is integrated in the solid microphone base. The aluminium base is equipped with two push-to-talk switches.

## TECHNICAL SPECIFICATIONS

|                                |                          |                         |                 |
|--------------------------------|--------------------------|-------------------------|-----------------|
| polar pattern                  | uni-directional          | buttons                 | 2 push to-talk  |
| indicator                      | 1 per button             | zones                   | 2               |
| frequency range                | 80 Hz - 12 kHz           | nominal output level    | 275 mV balanced |
| rated output impedance in ohms | 600 balanced             | mic stem lenght in mm   | 310             |
| connector                      | open wire                | cable lenght in m       | 5               |
| cable type                     | 2 core + 2 core screened | width in mm             | 125             |
| height in mm                   | 55                       | depth in mm             | 175             |
| weight in gr                   | 850                      | Net weight product (kg) | 0,92            |

MORE PICTURES

