

MP16-G

Compact sound projector



MP16-G is a 100 volt compact sound projector that produces a natural sound for background music and speech reproduction. This loudspeaker assures you that people hear and understand your messages or advertisements loud and clear in shopping streets, parking lots, loading docks or warehouses.

The MP16-G will stay rust-free thanks to its coated aluminium grille and bracket.

The woofer is a 5.25" coated paper dual cone.

The shape of the bracket allows installing without removing the bracket which, a time saving advantage. MP16-G combines a rugged housing with a good sound quality ideal for many industrial or professional applications, indoor as well as outdoors.

The MP16-G loudspeakers can be painted into any colour.


TECHNICAL SPECIFICATIONS

height in mm	138	width in mm	156
depth in mm	228	loudspeaker system	dual cone
woofer size in inch	5.25	woofer cone material	coated paper
mounting system	U-bracket	colour	grey
100V transformer power taps in watts	16 - 10 - 5	SPL 1W/1m in dB	91
max SPL 1m in dB	103	frequency response in Hz	100 - 18 k
main construction material	ABS plastic	grille main material	aluminium
IP rating	56	applicable low impedance	no
applicable in 100V	yes	Vertical dispersion angle 1000 Hz	180°
closest RAL colour (subject to deviations)	RAL9006	Net weight product (kg)	1.60

POLAR PLOTS


Data Shown: MP16 (Apart Audio)
Display Parameters: Frequency: 1000Hz (1/24th Octave)

Horizontal
Vertical




Data Shown: MP16 (Apart Audio)
Display Parameters: Frequency: 2000Hz (1/24th Octave)

Horizontal
Vertical




Data Shown: MP16 (Apart Audio)
Display Parameters: Frequency: 4000Hz (1/24th Octave)

Horizontal
Vertical



Data Shown: MP16 (Apart Audio)
Display Parameters: Frequency: 8000Hz (1/24th Octave)

Horizontal
Vertical



[MORE PICTURES](#)

