


NX 10

FULL-RANGE PASSIVE SPEAKER

NX series represents solid and powerful solutions for fixed installations as well as demanding mobile sound applications. NX full-range cabinets are based on top-line neodymium magnet transducers and high frequency drivers fitted with demodulation rings and copper caps for less distortions and improved voice coil cooling, allowing for prolonged high-SPL operation while preserving clarity and intelligibility.

NX 10 is a passive speaker based on 10" cone transducer and 1,5" HF driver. Speaker is equipped with pole mount adapter and M10 mounting points for various installation purposes and carefully designed cross-over network for ease of setup and use.



Main features:

- 500W nominal power
- 10" woofer with 3" voice coil
- 1,5" HF driver with 2,8" voice coil
- 133 dB Max SPL
- Pole mount adapter, M10 mounting points

Frequency Response (-10dB)	65 - 19000 Hz
Max SPL ¹	133 dB
Sensitivity (1W/1m)	97 dB
LF Driver	10", 3" VC
HF Driver	1,5", 2,8" VC
Nominal Coverage Angle (Horizontal x Vertical)	80 x 70 deg
Impedance	8 Ohm
Nominal power ²	500 W
Connectors	2x Neutrik Speakon
Dimensions (WxHxD)	319x610x336 mm
Net weight	19 kg
Shipping weight	22 kg
Mounting	10x M10 mounting points, 35mm pole socket
Enclosure material	Plywood; wear-resistant paint
Grill	Steel grill, polymer protective net

¹ - peak value, calculated according to AES 2 - 2012

² - based on transducer power measured according to AES 2 - 2012

With dedication to constant improvement of the products, manufacturer may change the listed specifications without prior notice