

# PTZOptics 20X Move 4K

The PTZOptics Move 4K offers built-in auto-tracking at resolutions up to 4K at 60fps (1080p at 60fps over 3G-SDI) and features a built-in tally light. Available outputs include SDI, HDMI, USB, and NDI@|HX for unrivaled performance and versatility. Compatible with most video production software, including OBS, vMix, Wirecast and more.

<http://ptzoptics.com/move-4k>

## Key Features:

- UltraHD 4K (3840x2160p) video resolutions up to 60 FPS
- Built-in auto-tracking capabilities
- 20X optical zoom lens with a 60.7° horizontal field of view
- Sony sensors offer high performance in low light scenarios with Wide Dynamic Range
- 3D noise reduction with our latest “low noise CMOS sensor”
- Serial (RS232 & RS485) & IP control (LAN/WAN)
- H.264, HEVC/H.265\*, & MJPEG video compression when IP streaming
- Simultaneous USB 2.0, HDMI 2.0 / 3G-SDI, NDI@|HX 3 / IP streaming (SRT, RTSP, RTMP) (HDMI & SDI are not simultaneous)
- PoE+ (Power over Ethernet) or 12VDC power supply
- Built in tally light
- Photobooth capable
- 5-year warranty



- What's in the Box:**

  - Camera
  - AC Power Supply
  - USB A-A Cable
  - RS232 Cable
  - Quick Start Guide
  - IR Remote
  - 2 AA Batteries

- |                        |                      |
|------------------------|----------------------|
| 1. Line in             | 7. DC 12V            |
| 2. Line Out            | 8. LAN (PoE)         |
| 3. Resolution Dial     | 9. USB 2.0           |
| 4. RS485 Interface     | 10. 3G-SDI Interface |
| 5. RS232 IN Interface  | 11. HDMI             |
| 6. RS232 OUT interface | 12. Restore          |

### Image Sensor & Lens

Video Sensor	1/1.8 inch, CMOS, Effective pixels: 8.42M
Resolution and Frame Rate	<b>HDMI:</b> 3840x2160p-60/59.94/50/30/29.97/25, 1920x1080p-60/59.94/50/30/29.97/25, 1920x1080i-60/59.94/50, 1280x720p-60/59.94  <b>SDI:</b> 1920x1080p-60/59.94/50/30/29.97/25, 1920x1080i-60/59.94/50, 1280x720p-60/59.94
Digital Zoom	Off (3840x2160), 2X (1920x1080), 3X (1280x720), 4X, (960x540), 8X (480x270), 16X (256x144)
Field of View	Horizontal: 3.5° (tele) ~ 60.7° (wide), Vertical: 1.9° (tele) ~ 34.1° (wide)
Min Lux	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
Lens	f = 6.25mm ~ 125mm, F1.58 ~ F3.95

### Pan / Tilt Movement

Pan Movement	±170°
Pan Speed	1.7° ~ 100°/s
Tilt Movement	+90° to -30°
Tilt Speed	1.7° ~ 69.9°/s
Presets	255 Presets
Video Tracking	Supported
Image Flip, Mirror and Freeze	Supported

### Power Options

Power Supply	DC 12V / PoE+ (802.3at)
Input Power	18W (Max)

### Physical Specifications








Material	Aluminum, Plastic
Color	Gray
Dimensions (W x D x H)	5.57 W x 5.94 x 7.91 in., 168.4 x 141.5 x 164.5 mm
Weight	3.25 lbs (1.47 kg)
Working Environment	Indoor
Operating Temperature	14°F ~ 104°F (-10°C to 40°C)
Storage Temperature	-40°F ~ 140°F (-40°C to 60°C)

### Rear Board Connectorstors







HD Video Output	1x RJ45: 10/100/1000M Adaptive Ethernet Port  1x HDMI: version 2.0  1x USB 2.0: type A  1x 3G-SDI: BNC type, 800mVP-p, 75Ω, Along to SMPTE 424M standard
Audio Interface	1x 3.5mm Line level Input
Communication Interface	1x 8 pin Mini-din RS232 input, Max distance: 98.5ft / 30m, protocol: VISCA / Pelco-D / Pelco-P  1x 8 pin Mini-din RS232 output, Max distance 98.5ft / 30m, protocol: VISCA / Pelco-D / Pelco-P  1x 2 pin Phoenix port, RS485 input / output, Max distance 3,937ft / 1200m, protocol: VISCA / Pelco-D / Pelco-P
Network Interface	RJ45: 10/100/1000M Adaptive Ethernet Port, supports PoE
Power Jack	JEITA type (DC IN 12V) Ethernet Port, support PoE

# PTZ OPTICS™







## Product Line

	PT12X-SE-GY-G3 PT20X-SE-GY-G3 PT30X-SE-GY-G3		PT12X-SE-WH-G3 PT20X-SE-WH-G3 PT30X-SE-WH-G3	1080p Image, 12X, 20X, or 30X optical zoom, HDMI, 3G-SDI, USB3-C, IP Streaming
	PT12X-4K-GY-G3 PT20X-4K-GY-G3 PT30X-4K-GY-G3		PT12X-4K-WH-G3 PT20X-4K-WH-G3 PT30X-4K-WH-G3	4K PTZ Camera, 12X, 20X, or 30X optical zoom, NDI® HX 3, HDMI, 3G-SDI, USB2-A, IP Streaming
	PT12X-LINK-4K-GY PT20X-LINK-4K-GY PT30X-LINK-4K-GY		PT12X-LINK-4K-WH PT20X-LINK-4K-WH PT30X-LINK-4K-WH	4K PTZ Camera, Dante™ AV-H ready, 12X, 20X, or 30X optical zoom, 3G-SDI, USB2-A, IP Streaming
	PT-STUDIOPRO			1080p Image, NDI® HX 3, 12X optical zoom & 16X digital zoom, Includes LED Panel Light

## Accessories

	HC-JOY-G4	Serial VISCA (RS232, RS485, Pelco-D, Pelco-P)
	PT-JOY-G4	VISCA over IP (PTZOptics & Sony) or Serial VISCA (RS232, RS485, Pelco-D, Pelco-P)
	PT-SUPERJOY-G1	VISCA over IP (PTZOptics & Sony), NDI®, Serial VISCA (RS232, RS485, Pelco-D, Pelco-P)
	IR Remote	Wirelessly control your camera with this included IR remote.
	Camera Management Platform	Control your PTZOptics cameras through one convenient, free desktop application
	PTZ Control Pro 2	The free PTZControl Pro 2 app offers easy control of PTZOptics cameras from any iOS device.

## Mounts

	HCM-1-BK		HCM-1-WH	Small Universal Wall Mount, mounts directly to wall or box with supplied hardware
	HCM-2-BK		HCM-2-WH	Large Universal Wall Mount, mounts directly to wall or box with supplied hardware
	HCM-1C-WH			Small Open Base Ceiling Mount, mounts to 1" NPT Pipe
	HCM-2C-WH			Large Open Base Ceiling Mount, mounts to 1" NPT pipe
	PT-WM-3-BK		PT-WM-3-WH	Large Wall Mount for Move 4K 30X, mounts directly to wall or box with supplied accessories
	PT-CM-1-BK		PT-CM-1-WH	Small Surface Ceiling Mount, mounts directly to ceiling or box w / supplied accessories
	PT-CM-3-BK		PT-CM-3-WH	Large Surface Ceiling Mount for Move 4K 30X, mounts directly to ceiling or box with supplied accessories