TG 500B

UHF Beltpack Transmitter

FEATURES

- Ergonomic design and programmable power lock
- Infrared interface to transmit settings from the receiver to the transmitter
- 4-pin male mini XLR connector for microphones or instruments
- LC display
- 3-stage gain switch
- Programmable mute button
- Battery power LED
- Operating time: approx. 10 hours with 2 x 1.5 V AA batteries
- Transmission range up to 120 m
- Synchronisation of receiver and transmitter in less than one second
- Charging contacts for WA-CD charger
- Removable belt clips for horizontal & vertical mounting
- Pilot tone function
- · Supplied with batteries and transport bag

DESCRIPTION

The ergonomic beltpack transmitters with a belt clip are practical in use with a weight of only 85 grams (without batteries). The transmission power can be switched between 10 mW and 50 mW. Settings are simple to configure on the receivers and are transmitted quickly and easily to the transmitters via infrared synchronisation. The integrated pilot tone function ensures interference-free transmission and warns when the battery power is running low. All transmitters are equipped with an LC display and have a programmable mute button.

A 10-hour battery operating time ensures uninterrupted operation, even during extended events. As an alternative to alkaline batteries, the transmitters can be operated with standard NiMH batteries, which can be recharged using the optional WA-CD charger without having to remove them from the transmitters.



TG 500B

VERSIONS

TG 500B	Beltpack transmitter, 518 – 548 MHz Order # 712.108
TG 500B	same as above,
	but 606 – 636 MHz Order # 712.116
TG 500B	same as above,
	but 794 – 832 MHz Order # 712.124
TG 500B	same as above,
	but 925 – 937.5 MHz* Order # 712.132
TG 500B	same as above,
	but 1,785 – 1,805 MHz Order # 712.140

^{*}For South Korean market only!

SETS

TG 510 Set consisting of: TG 500B beltpack transmitter, batteries and WA-CGI instrument cable TG 500SR single channel receiver with power adapter, two antennas and rack mount kit, 518 – 548 MHz Order # 712.388 TG 510 same as above, but 606 – 636 MHz . . . Order # 712.396 TG 510 same as above, but 794 – 832 MHz . . . Order # 712.418 TG 510 same as above, but 925 – 937.5 MHz* . Order # 712.426 TG 510 same as above, but 1,785 - 1,805 MHz. Order # 712.434 TG 534 Set consisting of: TG 500B beltpack transmitter, batteries and TG H34 headset (cardioid) TG 500SR single channel receiver with power adapter, two antennas and rack mount kit. 518 – 548 MHz Order # 712.442 TG 534 same as above, but 606 – 636 MHz . . . Order # 712.450 TG 534 same as above, but 794 – 832 MHz . . . Order # 712.469 TG 534 same as above, but 925 – 937.5 MHz* . Order # 712.477 TG 534 same as above, but 1,785 – 1,805 MHz. Order # 712.507 TG 558 Set consisting of: TG 500B beltpack transmitter, batteries and TG L58 clip-on microphone (omnidirectional) TG 500SR single channel receiver with power adapter, two antennas and rack mount kit, 518 – 548 MHz Order # 712.620 TG 558 same as above, but 606 – 636 MHz . . . Order # 712.639 TG 558 same as above, but 794 – 832 MHz . . . Order # 712.647

TG 558 same as above, but 925 – 937.5 MHz* . Order # 712.655

TG 558 same as above, but 1,785 – 1,805 MHz. Order # 712.663

2 of 2

TECHNICAL SPECIFICATIONS

Display	. LCD
Power supply	. 2 x AA NiMH or
	2 x 1.5 V alkaline batteries
Operating time	. approx. 10 hrs.
Ambient temperature	. 0 to +55 °C
Transmitting power	. 10 mW / 50 mW
Weight (without batteries)	. 85 g
Dimensions	. 90 x 59 x 26 mm
	(without antenna)
Pin assignment of 4-pin connector.	: 1
	■4 20k
	Audio
	2 o ^{+5V}
	1
	. ⊥ :

OPTIONAL ACCESSORIES

OI HOWAL 7	ICCESSORIES
Microphones	
TG L58 (TG)	Miniature condenser clip-on microphone, omnidirectional, water-resistant, with 4-pin mini XLR connector, blackOrder # 706.221
TG L58 tan (TG) TG H54 (TG)	same as above, but beige Order # 705.926 Condenser headset microphone, cardioid, black, with
TG H54 tan (TG) TG H74 (TG)	4-pin mini XLR connector Order # 708.313 same as above, but beige Order # 708.321 Neckworn microphone, condenser, cardioid, 4-pin mini XLR connector,
TG H74 tan (TG)	black
Charger WA-CD	Charger for handheld and beltpack transmitter with 4 charging compartments and control via Ethernet Order # 711.144
Cables WA-CGI	Connecting cable to connect

instruments with a mono



1/4" jack plug Order # 711.608

^{*}For South Korean market only!