

MAGEWELL

Ultra Stream SDI Technical Specifications

Copyright (c) 2011–2020 [Magewell Electronics Co., Ltd.](#) All rights reserved.

Specifications are based on current hardware, firmware and software revisions, and are subject to change without notice.

Windows is trademark or registered trademark of Microsoft Corporation.

Android is trademark or registered trademark of Google Corporation.

iOS is trademark or registered trademark of Apple Corporation.

Revised 03/09/2020

Supported Mobile Clients

- Android
 - Android 5.0 and above
- iOS
 - iOS 9.0 and above
- iPhone
 - iPhone 5s
 - iPhone SE
 - iPhone 6 / iPhone 6s / iPhone 6 Plus / iPhone 6s Plus
 - iPhone 7 / iPhone 7 Plus
 - iPhone 8 / iPhone 8 Plus
 - iPhone X
- iPod Touch
 - iPod Touch 5
 - iPod Touch 6

Supported Web Browser

- Microsoft Internet Explorer 11
- Microsoft Edge
- Mozilla Firefox version 61 and above
- Google Chrome version 49 and above
- Apple Safari 11.1 and above
- Opera 55.0.2994.44 and above

Input Interfaces

- BNC
 - SD/HD/3G SDI
- 3.5mm audio jack
 - Microphone interface

Output Interfaces

- BNC
 - SD/HD/3G SDI
- USB
 - USB 2.0
- 3.5mm audio jack
 - Headphone interface

Network Interfaces

- Wired Ethernet
 - 10/100/1000Mbps Ethernet
- Wi-Fi
 - IEEE 802.11 a/b/g/n/ac

- USB
 - USB 3G/4G Modem (not included)

Bluetooth

- Bluetooth 4.0 BLE

SDI Specific Features

- Support for SD/HD/3Ga/3Gb/3Gb-DL/3Gb-DS standards
- Support for 2K (2048x1080) input and loopthrough signals
- Support for 8/10/12-bit color depths
- Support for 60p, 60i, 50p, 50i, 30p, 25p signal formats
- Limited support for the first stream of 3Gb-DS
- Limited support for the first link of dual link interfaces
 - YCbCr 4:2:2 10-bit 1080p 50/59.94/60: output as 1080i 50/59.94/60
 - YCbCr 4:4:4 10-bit: output as 4:2:2
 - RGB 4:4:4: R/B sub-sampled

Analog Audio Features

- Extracting stereo embedded HDMI audio for recording, streaming and output via 3.5mm stereo mini-jack Line Out
- Recording and streaming analog audio from the 3.5 mm microphone interface

Encoding Features

- Support for H.264/HEVC (video) and AAC High Quality (audio) encoding
- Support for video bitrates of up to 8Mbps for the Main Stream and 1Mbps for the Sub Stream
- Support for encoding at input signal resolutions up to 1920x1080, including these lower resolutions: 1600x1200, 1440x1080, 1440x900, 1280x1024, 1280x960, 1280x800, 1280x720, 1024x768, 960x540, 800x600, 768x576, 720x576, 720x540, 640x480, 640x360, 480x360, 480x270 resolutions
- Support for 60fps, 59.94 fps, 50fps, 30fps, 29.97 fps, 25fps, 24fps, 15fps frame rates

Streaming Features

- Support for live streaming using RTMP protocol to software including Flash Media Server, Wowza, Red5 and Nginx server
- Support for RTSP protocol
- Streaming to Facebook, Twitch and YouTube platforms
- Support for streaming to multiple destinations, up to 2 servers simultaneously
- Support for specifying network priority when multiple networks are connected

Recording Features (to device & USB Flash Drive)

- Support for recording to USB Flash Drive and internal storage (32GB)
- Support for loop recording
- Support for auto-recording when the input signal is stable
- Support for recording video clips in different durations
- Support for recording as MP4 or MOV files
- USB Flash Drive file system formats: FAT32, NTFS, exFAT, VFAT
- Support for downloading video clips which are stored in device storage using the WebUI

Recording Features (to Mobile Device)

- Support for recording at up to 1280x720, 30fps
- Support for recording as MP4 files
- Taking still image snapshots during recording
- Saving recording files and screenshots to system album
- Previewing the main and sub streams
- Timer recording: 15s, 30s, 1min, 2min, 5min

Remote Control Features in App

- Support for connecting the device via Wi Fi, wired network, and device hotspot (i.e. AP mode)

- Support for connecting the smart phone Wi-Fi to the device hotspot (i.e. AP mode)
- Support for remotely controlling the device using WebUI and app
- Support for remotely checking the device status
- Support for setting volume, network, recording and live streaming parameters
- Support for checking and safely updating device firmware (or resetting to the factory firmware version)
- Support for simultaneous main stream and sub stream encoding with customizable parameters
- In-app online help
- Support for multiple users logging-in simultaneously
- Support for device configuration using the WebUI

LED Indicator

- Indicates the state of the input signal, Ethernet Network, Wi-Fi, USB flash drive
- Indicates the working state of the device: startup, recording, streaming, updating

Form Factor

- 94.20mm x 94.20mm x 22.30mm

Accessories

- AC adapter

Power Supply and Consumption

- Power port
 - 5V/2A
 - 2.1mm x 5.5mm socket, centre pin positive
- Max power consumption: ~6.0 W

Working Environment

- Operating temperature: 0 to 40 deg C
- Storage temperature: -20 to 70 deg C
- Relative humidity: 5% to 90% non-condensing