

DATA SHEET

IMPERA UNIFORM

8-BUTTON E INK CONTROL PAD WITH ETHERNET PORT

The Impera Uniform control pad is a compact, highly customizable AV control suitable for wall-mounting. It provides a simple and intuitive interface for presentation spaces, learning environments, and conference rooms, regardless of the type of equipment installed.

Equipped with a software configurable E Ink display, the Uniform can be quickly programmed and customized within Project Designer as the needs of the room change over time, making the Uniform a very flexible and cost effective control solution.



FEATURES

- Supports up to 8 software-configurable buttons
- 2.7-inch high contrast E Ink display
- Includes on-board controller; no external processor required
- 1 bi-directional RS-232 port for third party control with feedback
- 2 uni-directional RS-232 ports for third party control
- 3 GPIO ports
- Supports email notifications for lamp/filter hours and warnings
- Micro USB connection for system configuration and maintenance
- Expansion Bus supports up to 8 additional devices (keypads and port expanders)
- PoE powered (IEEE 802.3at Class 1, 4W) for simple, single CAT5e/CAT6 cable installation
- Covered by Biamp Systems' five-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The control pad shall include 8 mechanical buttons for initiating control functions. The control pad shall include 8 multicolor, software configurable LEDs. Each mechanical button shall have a corresponding LED. The control pad shall include a high contrast E Ink display for function identification and labeling. The control pad shall utilize an Ethernet network via an RJ-45 connector for networking as well as software configuration and control. The control pad shall include 1 bi-directional RS-232/IR port for controlling third party devices with feedback functionality and shall be software programmable. The control pad shall include 2 uni-directional RS-232/IR ports for controlling third party devices and shall be software programmable. The control pad shall include 3 channels of General Purpose Input and Output connection (GPIO) for sending or receiving logic signals. The programming of the GPIO ports shall be software configurable. The control pad shall include 1 micro USB port for local system configuration and maintenance. The control pad shall be made from white PVC/ABS material with UV protection additive. The control pad shall be powered by PoE (IEEE 802.3at Class 1, 4W). The control pad shall be CE marked and shall be compliant with the RoHS directive. Warranty shall be five years. The control pad shall be the Impera Uniform.

IMPERA UNIFORM SPECIFICATIONS

Display		Expansion Bus	
Display Type:	High-Contrast 2.7" E Ink display	Output Power:	12 V DC (0.3 A)
Resolution:	264 x 172 pixels	Number of Devices Supported:	8
Color:	Black/white	Ethernet	
Control		Port Speed:	10/100 Mbps
Button Quantity:	8	Autosense:	Yes
Button Type:	Mechanical	Number of Devices Supported:	2
LED Indicators:	Multi-color	Power:	PoE (IEEE 802.3at Class 1, 4W)
GPIO		Power Consumption:	< 4W Max
I/O Quantity:	3	Included Accessories:	In-wall mounting bracket Mounting screws and wall plugs
Sense Low:	< 1 VDC	Overall Dimensions	
Sense High:	> 4 VDC	Height:	3.7 inches (94 mm)
Output Type:	Open drain	Width:	3 inches (76 mm)
Max Voltage:	24 VDC	Depth:	0.6 inches (15 mm)
Max Current:	0.5 A	Weight:	0.2 lbs (84 g)
RS-232 / IR		Environmental	
Number of Ports:	1 (bidirectional) 2 (unidirectional)	Ambient Operating Temperature Range:	32 - 104° F (0 - 40° C)
Baud Rate:	1200 - 115200 bit/sec	Humidity:	10-90% relative humidity (non-condensing)
Data Bits:	7, 8	Altitude:	0-6,600 ft (0-2000m) MSL
Parity:	Even, Odd, None	Compliance	
Stop Bits:	1, 1.5, 2	CE Marked (Europe) RoHS Directive (Europe)	
IR Frequency Range:	381 Hz to 500 kHz		

OPTIONAL ACCESSORIES



KP-U8-RP

US/UK wall adaptor plate



KP-U8-WB

Angled wall mount

Biamp and Impera are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.