

VCA-202 - Volume Control

482 mm
19"



Voltage-controlled 2-channel VCA volume control

- 2-channel mono operation or stereo operation
- Remote control for each channel via optional wall-mounted volume control VCA-202RN or via lin. 10 k Ohm potentiometer (not supplied), control voltage: 0-10 V DC current
- 10 V voltage output for potentiometer
- Servo-balanced inputs and outputs
- 482 mm (19") rack installation, 1 RS

For the remote volume control of PA systems in large areas (e.g. churches, workshops). The volume control VCA-202 is inserted between preamplifier and power amplifier.

The surface-mounted housing ATT-300 can be used for universal mounting of the potentiometers.

Technische gegevens:

Line input, mono	: 1 V/30 k Ohm
Input control voltage	: 0-10 V DC current /100 k Ohm
Line output, mono	: 1 V/600 Ohm
Output control voltage	: 10 V DC current /5 mA
Frequency range	: 20-20,000 Hz
THD	: 0.1 %
S/N ratio	: 70 dB
Power supply	: 230 V~/50 Hz/10 VA
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 482x48x105 mm, 1 RS
Weight	: 1.5 kg
Line input, mono	: 2 x XLR, bal.
Input control voltage	: plug-in screw connection
Line output, mono	: 2 x XLR, bal.
Output control voltage	: plug-in screw connection