

VM-22H

2x1:2 Compact HDMI Switchable DA

| HDMI | HDCP Compliant



The VM-22H is a distribution amplifier for HDMI signals. The unit reclocks and equalizes one of two selectable input signals and distributes it to two identical outputs

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)

HDCP Compliant

HDMI Support - Deep Color, x.v.Color™, Lip Sync, CEC

3D Pass-Through

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems

Active Output LED Indicators

Control - Front panel or IR remote switching

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances

Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter



TECHNICAL SPECIFICATIONS

INPUTS: 2 HDMI connectors

OUTPUTS: 2 HDMI connectors

BANDWIDTH: 6.75Gbps (2.25Gbps per graphic channel)

HDMI STANDARD:

COMPLIANCE WITH Supports HDMI and HDCP

CONTROLS: EDID SETUP button, input select button, IR

INDICATOR LEDs: IN 1, IN 2, OUT 1, OUT 2, and ON LEDs

POWER

CONSUMPTION:

5V DC, 910mA

INCLUDED ACCESSORIES: Power supply, bracket installation kit, IR remote control

OPTIONS: HDMI/HDMI male-to-male cables

PRODUCT DIMENSION: 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT: 0.3kg (0.7lbs) approx

SHIPPING

15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.6kg (1.2lbs) approx

