




# ASSEMBLY INSTRUCTION

**SCD-W | Rubber sealing cover D-Series**

**SCNAC-FPX | Rubber sealing cover powerCON NAC3FPX**

**SCNAC-MPX | Rubber sealing cover powerCON NAC3MPX**



**ATTENTION:**  
Maximum allowable torque  
 $M_A = 40 \text{ Ncm}$

NEUTRIK AG	LI	T: +423 / 237 24 24	F: +423 / 232 53 93	NEUTRIK France	FR	T: +33 1 / 4131 6750	F: +33 1 / 4131 0511
NEUTRIK USA Inc.	USA	T: +1 704 / 972 3050	F: +1 704 / 438 9202	NEUTRIK Tokyo Ltd.	JP	T: +81 3 / 3663 4733	F: +81 3 / 3663 4796
NEUTRIK (UK) Ltd.	UK	T: +44 1983 / 811 441	F: +44 1983 / 811 439	NEUTRIK Hong Kong Ltd.	HK	T: +852 / 2687 6055	F: +852 / 2687 6052
NEUTRIK Vertriebs GmbH	DE/NL/AT/DK	T: +49 8131 / 280 890	F: +49 8131 / 280 830				

Draft. Nr.: BDA 374 / 3102M2161 | Update: 22.05.2013 | Data subject to change without prior notice. ©2013 NEUTRIK®. ALL RIGHTS RESERVED. NEUTRIK® are registered trademark.

[www.neutrik.com](http://www.neutrik.com)

**NEUTRIK®**